

The Alumax 393CV-PS Custom Stikstall Shower Door with a frameless door is custom fabricated to exact opening dimensions. It easily adapts to buttress conditions.

Features include 1/4" glass in door, a 6" back to back formed metal handle, top magnetic closure, polycarbonate strike and a clear vinyl drip rail, all of which add an upscale look to the bath environment.

The 393CV-PS Stikstall Shower Doors are available in satin, silver, gold and brushed nickel anodized finishes, as well as, an array of powder paint colors including oil rubbed bronze.

393CV-PS Stikstall Shower Door - Frameless Door



PRODUCT FEATURES

Available in standard and custom configuration. Tempered safety glass.

Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb.

Hinge assembly has a molded bushing attached at the top and bottom of door panel

SIZE LIMITATIONS

Maximum allowable width of unit = 48 x 48 Maximum allowable height of unit = 84

PARTS LIST

- 2 Curb Sections (with weep slots) Α.
- 2 90° Anchor Plates with screws Β.
- C. 16 #6 x 3/8 Truss Head Screws
- 2 Header Sections D.
- E. 3 Wall Jambs
- 6 Plastic Wall Anchors F.
- G. 6 #8 x 1-1/2 Truss Head Screws
- Η. 4 Plastic Setting Blocks
- **Continuous Hinge Jamb** Ι.
- 2 Fixed Glass Panels J.
- H Strike Jamb Polycarbonate K.
- Strike Jamb L.
- M. Deflector
- 1 Glazed Door Panel N.
- Q. Continuous Hinge Rail
- R. V-266 Vinyl
- 1 Snap-in Fillers S.
- 1 Handle Vinyl Τ.
- U. 1 Latch
- V. 2 Tubular Handles
- X. 4 Plastic Washers
- Y. 5" Magnet
- AA. 2 Plastic Bushings
- BB. 2 Cone Head Bolts
- CC. 2 Set Screws
- GG. Vertical Glazing Vinyl
- HH. Horizontal Glazing Vinyl



This enclosure includes a SC-922 Header. Profile pictured above.



