Alumax



The Alumax 395CV Custom Stikstall Shower Door with a frameless door is custom fabricated to exact opening dimensions. It easily adapts to buttress conditions.

Features include 1/4" glass in door, a 6" back to back formed metal handle, magnetic closure and a clear vinyl drip rail, all of which add an upscale look to the bath environment.

The 395CV Stikstall Shower Doors are available in satin, silver, gold and brushed nickel anodized finishes, as well as, an array of powder paint colors including oil rubbed bronze.

395CV Stikstall Shower Door - Frameless



PRODUCT FEATURES

Available in standard and custom configuration. Tempered safety glass.

Door has a continuous extruded ball and socket hinge that is intrgral to the hinge rail and jamb. Hinge assembly has a molded bushing attached at the top and bottom of door panel.

SIZE LIMITATIONS

Maximum allowable width of unit = 72 Maximum allowable height of unit = 84

PARTS LIST

- A. 1 Curb Section
- B. 2 Wall Jambs
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1-1/2" Truss Head Screws
- E. 4 Plastic Setting Blocks
- F. 2 Fixed Glass Panels
- G. 2 180° Posts
- H. 1 Header
- I. Continuous Hinge Jamb
- J. 14 #6 x 3/8" Truss Head Screws
- L. 1 Glazed Door Panel
- M. 2 Snap-in Fillers
- N. 1 Strike Jamb (Magnetic)
- P. 1 Handle Vinyl
- Q. Continuous Hinge Rail
- R. 1 Latch
- S. 2 Tubular Handles
- T. 4 Plastic Washers
- U. 2 Plastic Bushings
- V. 2 Cone Head Bolts
- W. 2 Set Screws
- X. 1 Deflector
- EE. Vertical Glazing Vinyl
- FF. Horizontal Glazing Vinyl

